Wheel loader RT100/100D

For Earth, For Life




Standard Equipment	RT100	RT100D
Tyres 23 x 8.50-12 Skid	V	~
Transmission hydrostatic 4 wheel drive with automotive control	/	✓
Driving system: 4 hydraulic wheel motors	/	✓
Differential lock: electric controlled	'	✓
Electric shuttle on joystick	/	/
Front attachment controlled by joystick	✓	✓
Auxiliary circuit 1 at front end-double acting - mechanically activated	✓	✓
Floating position	'	/
ROPS / FOPS canopy	'	/
Deluxe seat with safety belt, armrest and extended backrest	'	/
Lifting hooks	✓	✓
2 Working lights on arm	✓	✓
1 Working light at rear		✓
Parallel Indicator on tilt cylinder		✓
Main switch	V	~
Free return hydraulic oil		~
Towing hook		~
Cyclone filter	V	'
Oil Cooler	V	'
Traffic homologation kit (traffic lights and mirrors)	V	✓
Parking brake: hydraulic multidisc brake	V	✓
Mechanical quick-hitch compact	V	
Hydraulic quick-hitch compact		✓

Specifications

For Earth, For Life


Kıj	ho	to
- /->	- 」 - 」	1.4

Model name			RT100/D
Engine	Make		
	Model	D722	
Displacement C		CC	719
	Output	HP(kW)	20(15)
Service weight		kg	1100
Tipping load		kg	1000
Driving speed		km/h	0~15
Lifting capacity	Α	kg	1000
	В	kg	800
	С	kg	550
Auxiliary circuit	Oil flow	LT/Min	28
	Oil pressure	Bar	180



Dimensions

Model name			RT100/D
Α	Wheel base	mm	1205
В	Overall lenth w/o bucket	mm	2200
С	Overall height with canopy	mm	2060
D	Overall width	mm	960
Е	Height front frame	mm	1380
F	Max. dumping height	mm	1408
G	Max. bucket pin height	mm	2170
Н	Height with bucket	mm	2976



Basic accessories

Earth bucket



Pallet fork





Kubota Europe S.a.s. 19-25 rue Jules Vercruysse BP 50088- Z.I. 95101 Argenteuil Cedex France Tel: +33(0)1 34 26 34 34

Fax: +33(0) 1 34 26 34 34 Fax: +33(0) 1 34 26 34 21 www.kubota.fr